

OPEN POCKET SOFT MOUNT

HIGH SPEED WASHER-EXTRACTOR

CSL110



INDUSTRIAL STRENGTH WASHER-EXTRACTOR

SPECIFICATIONS

Model	CSL110
Capacity	110 lb.
Cylinder Size	39" x 26"
Cubic Content	17.9 cu. ft.
Door Opening	20-1/4"
Water Inlets (Hot & Cold)	3/4" NPT
Drain	4" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 750 RPM
G-Force at High Extract	up to 310 G
Extract Motor	10 h.p.
Circuit Breaker	30 Amp
Control	HMi Touch Screen
Programs	50
Features	Productivity Reporting
Dimensions (overall)	
Width	52"
Depth	56-3/4"
Height	67"
Net Weight	3,968 lb.
Shipping Weight	4,070 lb.

Standard voltage is 230/3/60. Consult factory for other available electrical voltages. Consult factory for installation drawings for specific models. Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN



AVAILABLE WITH THE REVOLUTIONARY

DYNOZONE - DYNAWASH® OZONE SYSTEM



BATTLESHIP QUALITY

WWW.EDRODYNAWASH.COM

The EDRO Corporation

37 Commerce Street - P.O. Box 308 East Berlin, CT 06023-0308 USA Fax (860) 828.5984 Phone (860) 828.0311