

## **OPEN POCKET SOFT MOUNT**

HIGH SPEED WASHER-EXTRACTOR



## INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS



Model	CSL175
Capacity	175 lb.
Cylinder Size	45" x 32"
Cubic Content	29.4 cu. ft.
Door Opening	23-1/2"
Water Inlets (Hot & Cold)	1-1/2" NPT
Drain	5" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 700 RPM
G-Force at High Extract	up to 315 G
Extract Motor	15 h.p.
Circuit Breaker	30 Amp
Control	HMi Touch Screen
Programs	50
Features	Productivity Reporting
Dimensions (overall)	
Width	62-1/8"
Depth	72-1/8"
Height	73-1/2"
Net Weight	5,952 lb.
Shipping Weight	6,052 lb.

Standard voltage is 230/3/60. Consult factory for other available electrical voltages. Consult factory for installation drawings for specific models. Field programmable speeds.



DynOzone

AVAILABLE WITH THE REVOLUTIONARY

DYNOZONE - DYNAWASH® OZONE SYSTEM



**EQUIPPED WITH DYNATROL HMI TOUCH SCREEN** 

WWW.EDRODYNAWASH.COM

The EDRO Corporation

37 Commerce Street - P.O. Box 308 East Berlin, CT 06023-0308 USA Fax (860) 828.5984 Phone (860) 828.0311