

OPEN POCKET SOFT MOUNT HIGH SPEED WASHER-EXTRACTOR

CSL225

INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS

Model	CSL225
Capacity	225 lb.
Cylinder Size	49" x 33"
Cubic Content	35.9 cu. ft.
Door Opening	25"
Water Inlets (Hot & Cold)	1-1/2" NPT
Drain	5" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 650 RPM
G-Force at High Extract	up to 293 G
Extract Motor	20 h.p.
Circuit Breaker	50 Amp
Control Programs	HMI Touch Screen 50
Features	Productivity Reporting
Dimensions (overall)	
Width	64"
Depth	74-1/4"
Height	69-1/4"
Net Weight	6,393 lb.
Shipping Weight	6,593 lb.



Standard voltage is 230/3/60. Consult factory for other available electrical voltages.
Consult factory for installation drawings for specific models.
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

DynOzone

AVAILABLE WITH THE REVOLUTIONARY
DYN-OZONE - DYNAWASH® OZONE SYSTEM



BATTLESHIP QUALITY

WWW.EDRODYNAWASH.COM

Technical specifications are based on the latest information available at the time of printing and are subject to change without notice.
Manufactured in accordance with Canadian Standards Association (CSA) general requirements

The EDRO Corporation
37 Commerce Street - P.O. Box 308
East Berlin, CT 06023-0308 USA
Fax (860) 828.5984 Phone (860) 828.0311

DBCSSL225PDF-2013