

**OPEN POCKET SOFT MOUNT  
HIGH SPEED WASHER-EXTRACTOR**

**CSL350**

**INDUSTRIAL STRENGTH WASHER-EXTRACTOR  
SPECIFICATIONS**



Model	CSL350
Capacity	350 lb.
Cylinder Size	58" x 38"
Cubic Content	58.1 cu. ft.
Door Opening	30"
Door Tilting	15 degree L/U
Water Inlets (Hot & Cold)	2" NPT
Drain	2 @ 5" O.D.
Drive System	Inverter with Single Motor
G-Force at High Extract	up to 324 G
High Extract	up to 625 RPM
Circuit Breaker (@220v)	100 Amp
Control Programs	HMI Touch Screen
Features	50 Productivity Reporting
<b>Dimensions</b> (overall)	
Width	79"
Depth	92"
Height	89-3/4"
Net Weight	13,228 lb.

Model shown with optional forward tilting and autoswing door.  
Consult factory for other available electrical voltages.  
Consult factory for installation drawings for specific models.  
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN



AVAILABLE WITH THE REVOLUTIONARY  
DYNOZONE - DYNAWASH® OZONE SYSTEM



BATTLESHIP QUALITY

[WWW.EDRODYNAWASH.COM](http://WWW.EDRODYNAWASH.COM)

**The EDRO Corporation**

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311