

**OPEN POCKET SOFT MOUNT
HIGH SPEED WASHER-EXTRACTOR**

CSL60

**INDUSTRIAL STRENGTH WASHER-EXTRACTOR
SPECIFICATIONS**

<i>Model</i>	<i>CSL60</i>
Capacity	60 lb.
Cylinder Size	32" x 20"
Cubic Content	9.3 cu. ft.
Door Opening	17"
Water Inlets (Hot & Cold)	3/4" NPT
Drain	4" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 810 RPM
G-Force at High Extract	up to 297 G
Extract Motor	7.5 h.p.
Circuit Breaker	30 Amp
Control	HMI Touch Screen
Programs	50
Features	Productivity Reporting
Dimensions (overall)	
Width	45-1/4"
Depth	49-3/4"
Height	60-1/4"
Net Weight	3,300 lb.
Shipping Weight	3,400 lb.



Standard voltage is 230/3/60. Consult factory for other available electrical voltages.
Consult factory for installation drawings for specific models.
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN



AVAILABLE WITH THE REVOLUTIONARY
DYNOZONE - DYNAWASH® OZONE SYSTEM



BATTLESHIP QUALITY

WWW.EDRODYNAWASH.COM

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311