

OPEN POCKET RIGID MOUNT HIGH SPEED WASHER-EXTRACTOR

NX40

INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS



Model	NX40-TV
Capacity	40 lb.
Cylinder Size	30" x 16"
Cubic Content	6.5 cu. ft.
Door Opening	15"
Water Inlets (Hot & Cold)	3/4" NPT
Drain	3-1/8" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 700 RPM
G-Force at High Extract	up to 209 G
Extract Motor	3 h.p.
Circuit Breaker	15 Amp
Control Programs	HMI Touch Screen
Features	50 Productivity Reporting
Dimensions (overall)	
Width	34"
Depth	38-1/4"
Height	56-1/2"
Net Weight	850 lb.
Shipping Weight	890 lb.

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.
Consult factory for installation drawings for specific models.
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

DynOzone

AVAILABLE WITH THE REVOLUTIONARY
DYN-OZONE - DYNAWASH® OZONE SYSTEM



BATTLESHIP QUALITY

WWW.EDRODYNAWASH.COM

The EDRO Corporation

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311