

## OPEN POCKET RIGID MOUNT HIGH SPEED WASHER-EXTRACTOR

# NX60

### INDUSTRIAL STRENGTH WASHER-EXTRACTOR SPECIFICATIONS



Model	NX60-TV
Capacity	60 lb.
Cylinder Size	32" x 20"
Cubic Content	9.3 cu. ft.
Door Opening	17"
Water Inlets (Hot & Cold)	3/4" NPT
Drain	3-1/8" O.D.
Drive System	Inverter with Single Motor
High Extract	up to 700 RPM
G-Force at High Extract	up to 222 G
Extract Motor	5 h.p.
Circuit Breaker	20 Amp
Control	HMI Touch Screen
Programs	50
Features	Productivity Reporting
<b>Dimensions</b> (overall)	
Width	35"
Depth	44"
Height	64"
Net Weight	1,250 lb.
Shipping Weight	1,300 lb.

Standard voltage is 230/3/60. Consult factory for other available electrical voltages.  
Consult factory for installation drawings for specific models.  
Field programmable speeds.



EQUIPPED WITH DYNATROL HMI TOUCH SCREEN

## DynOzone

AVAILABLE WITH THE REVOLUTIONARY  
DYN-OZONE - DYNAWASH® OZONE SYSTEM



BATTLESHIP QUALITY

[WWW.EDRODYNAWASH.COM](http://WWW.EDRODYNAWASH.COM)

**The EDRO Corporation**

37 Commerce Street - P.O. Box 308

East Berlin, CT 06023-0308 USA

Fax (860) 828.5984 Phone (860) 828.0311